



CFC-250-TE-AIC

Thermoelectric Liquid Recirculating Chiller

Features

- Precise temperature control
- Green devices
- Reliable solid-state operation
- Low noise producing
- Compact design
- Low fluid level warning



Applications

- Medical Imaging Systems
- Medical Lasers
- Photonics Laser Systems
- Analytical & Industrial Instrumentation
- Laboratory applications
- Biomedical Systems
- Food industry



Type	CFC-250-TE-AIC
Voltage VAC 50/60 Hz	100VAC/240VAC
Current, Amps. @ 110/220 VAC	2,6/ 1,3
Ambient temperature, °C	(+4 ÷ +45)°C
Cooling capacity at dT=0, Watt ¹	248 W
Operating temperature range of fluid: - coolant – distilled water, °C	(+2 ÷ +40)°C
Operating temperature range of fluid: - coolant 70% distilled water H2O + 30% ethylene glycol or ethanol, °C	(-12 ÷ +40)°C
Control accuracy, °C	±0,10°C
Fans lifetime (at temperatures not higher than +40°C) and nominal voltage	≥60,000 hours
Volume of inside liquid circuit, ml	650 ml
Reservoir, ml	450 ml
Type of coolants ²	Distilled water, 70% distilled water H2O + 30% ethylene glycol or ethanol, others non-corrosive coolants
Operating mode	Continuous
Setup tuning	Keypad and via RS485
Protection of air heatsink against corrosion	Anodizing on aluminum 6 to20 microns
Corrosions protection of liquid heat exchanger	galvanic nickel plating
Dimensions (height/width/depth), mm	310/215/380
Weight ³	11,5 kg

1 - Cooling capacity is rated at ambient temperature +35°C for liquids with thermal conductivity 4.19 +/- 5%, kJ/(kg*K).

2 - Used Coolant used should have no components capable of forming deposits or corrosion of the fins, as well as to dissolve nickel coating; should not be exposed to freezing or boiling over the temperature range of the liquid circuit.


3 - Weight can deviates from indicated within +/-5%.

Contact us for more information
e-mail: info@crystalltherm.com

+7-495-664-24-31 , +7-495-519-88-52 , +7-495-519-00-69

Fax: +7-495-515-40-94


Performance



$dT = T_{\text{ambient air temperature}} - T_{\text{liquid}}$.

Q - cooling capacity, W, @ ambient temperature +35° C.

PUMP CURVE



Mechanical Drawings

